

SPEC SHEET

PUMP TYPE	Bore		V belt drive				Coupling drive							
			Capacity	Pressure	Speed	4P Motor	50 Hz				60 Hz			
	L/min	MPa					min ⁻¹	kW	L/min	MPa	min ⁻¹	kW	L/min	MPa
	B	A												
HP-4(M)	3/4	20	10	0.5~1.0	500	0.4~0.75	22	0.5~1.0	960	0.75~1.5	26	0.5~1.0	1150	0.75~1.5
HP-6(M)	1	25	20	0.5~1.0	500	0.75~1.5	45	0.5~1.0	960	1.5~2.2	54	0.5~1.0	1150	1.5~3.7
KH-10(M)	1 1/2	40	45	0.5~1.0	500	1.5~2.2	100	0.5~1.0	960	2.2~5.5	120	0.5~1.0	1150	3.7~5.5
KH-15(M)	2	50	90	0.5~1.0	500	2.2~3.7	190	0.5~1.0	960	3.7~7.5	230	0.5~1.0	1150	5.5~7.5
KH-25(M)	3	80	150	0.5~1.0	450	3.7~7.5	340	0.5~1.0	960	7.5~15	400	0.5~1.0	1150	7.5~15
KH-30(M)	4	100	200	0.5~1.0	450	5.5~11	450	0.5~1.0	960	11~22	540	0.5~1.0	1150	11~22
KH-35(M)	4	100	270	0.5~1.0	450	7.5~15	620	0.5~1.0	960	15~26	740	0.5~1.0	1150	15~26
KH-50(M)	5	125	400	0.5~1.0	450	11~22	850	0.5~1.0	960	22~37	1000	0.5~1.0	1150	22~37
KH-60(M)	5	125	550	0.5~1.0	450	15~26	1200	0.5~1.0	960	26~45	1400	0.5~1.0	1150	26~45

Note: This specification is for viscosity of approximately 300 mPa·s.